

DFFICE OF THE MARION COUNTY SURVEYOR SECTION RECORD CORNER SECTION 22 TOWNSHIP 14 RANGE 5 DATE:2-24-98 5-6-05 PARTY CHIEF: Kiste CREW: TYPE OF MARKER: 4x4. ****Harrison SEE. NOTE: METHOD OF ESTABLISHMENT: County:	
IN. S.P.C. E ZONE, NAD 83 NAME: 14052209 broken post 10" dn set new 6x6" post next to a 4x4" conc. monument w/ 5/8" reb in the middle as the corner monument.	9000 S
Line of E County Line 12000 E	2. 3.

Driginal post set 1820 by Hendricks with witnesses: 6" ash \$ 78 \ W 6 links, 4" dogwood N 11 E 32 links per Marion County Atlas pg. 13. Hosbrook 12-18&19&20-1850 called no stone but witness: 34" beech N 33 W 41 links per Franklin Township Legal Survey Book pg. 45. 10-11-91 Shelby Co. Surveyor's office called PK nail in concrete for corner post. PK nail was 10" below surface on W side of 6" rotten wooden post. 2-24-98 a new 6"x6" wooden post was set next to a 4"x4" concrete monument with a 5/8" rebar in the middle as the corner monument by Kiste.

HC452209

REF.	DISTANCE	DESCRIPTION
1.	15.65'	Boat spike W 12" ash 48" up
2.	10.60'	Bolt spike w/washer SW 8" ash 60"up
3.	27,42'	Bolt spike w/washer NE 18' ash 60'up